

## TEXOL TECHNICAL WHITE OIL (WOT)

TEXOL WOT Oils are severely refined hydro-cracked / hydro-treated oils with highest degree of purity and are stabilized with suitable additives for oxidation/UV stability. These oils are suitable for Industrial applications. The below oils are also recommended for Polystyrene and Thermoplastic industry.

TEXOL WOT Oils are offered in 200-250 liters' net HDPE / Steel Drums /IBC & in bulk Flexi bags or ISO tanks.

Test Description	Test Method	Specification Limits								
		TEXOL WOT 60	TEXOL WOT 70	TEXOL WOT 80	TEXOL WOT 100	TEXOL WOT 150	TEXOL WOT 180	TEXOL WOT 250	TEXOL WOT 350	TEXOL WOT 500
Appearance	Visual	Transparent clear, colorless, odorless liquid free from suspended impurities								
Colour, Saybolt	ASTM D 156	+30								
Density @ 25 °C gm/ml	ASTM D 1298	>0.810	>0.820	>0.822	>0.820	>0.820	>0.835	>0.835	>0.850	>0.855
Kin. Viscosity @ 40 °C, cSt	ASTM D 445	7-11	11-14	14-17	18-23	27-33	30-35	36-45	68-72	80-85
Flash Point°C min	ASTM D 92	145	150	160	180	180	190	190	200	220
Pour Point°C, max	ASTM D 97	-15	-15	-15	-12	-12	-12	-12	-12	-12